

The headset parts may be cleaned with mild soap and water using a soft cloth. Then dry immediately. **Caution: Do Not immerse** any part of the headset in water or any other liquid. Be especially careful not to allow the microphone to become wet! Exposure to moisture may cause internal corrosion and failure and will void your manufacturers warranty.

Cleaning will help the headset maintain its "like new" condition for many years.

WINDSCREEN

The microphone windscreen will reduce annoying wind noise and breath pops picked up by headset microphones. It also protects the microphone element from dirt and moisture. The windscreen should be washed regularly to maintain hygiene and avoid clogging. Wash in warm water and mild soap. Rinse thoroughly and make sure it is completely dry before putting it back on.

To remove the windscreen, carefully grasp the windscreen lightly along its entire length and remove from the microphone element being careful not to twist the element itself.

Put the windscreen on the microphone by gently pulling from the open end. Do not pull it so tightly that it stretches against the end of the microphone.

WARRANTY

Your headset is covered by a limited five-year parts and labor warranty. Please see the enclosed warranty card for details.

You may refer to the parts list on the reverse side, if you choose to replace parts yourself. The parts list describes parts for this particular headset only. Parts lists for other models are available on our Web Site or can be obtained by contacting Sigtronics Corporation.



Sigtronics Corporation
178 East Arrow Highway
San Dimas, CA 91773
Phone: 909 305-9399
E-mail: info@sigtronics.com
Web Site: www.sigtronics.com

Model S-18 Headset Instructions

The S-18 series headset is adjusted at the factory for immediate use. Headsets equipped with two plugs are the standard configuration. The headphone plug is the larger diameter plug and should be inserted into the headphone jack (.250" standard monaural jack). The mic plug is the smaller diameter plug and should be inserted into the microphone jack (.206" standard microphone jack).

The headband is adjustable through a full range of motion, or the locking nuts may be tightened to allow you to custom fit the headset. Place the headset over your head, adjust the slide up until minimum pressure is felt on the top of your head. The headset is now properly adjusted. For maximum noise attenuation, the clamping pressure of the headband has been set at the factory. Releasing the clamping pressure by bending the headband is not advised, because loss of attenuation will result.

The microphone boom is fully adjustable and will rotate 180 degrees for use on the left or right side of the head.


Make sure you are speaking into the side of the mic labeled "Talk" or substantial loss of gain will occur. Microphone placement should be at the corner of the mouth, approximately ¼" from the lips.

When you first connect the headset, turn the volume control on the headset up to the full clockwise position then adjust the listening volume with the audio control of either your radio or intercom as appropriate. Passengers should also turn their individual headset volumes up fully. Doing this allows for a full range of adjustment for each passenger, since those with the most acute hearing can turn their headset volume down, if necessary.

continued on back...



...when it counts!



SIGTRONICS S-18 HEADSET PARTS IDENTIFICATION BREAKDOWN

ITEM	P/N	DESCRIPTION	ITEM	P/N	DESCRIPTION	ITEM	P/N	DESCRIPTION
1	800192	PREAMP	12	100364	SCREW, 8-32 X 3/8, PHILLIPS HEAD	23	100379	FOAM, SOUND ATTENUATING, RECEIVER COVER, 1/4 INCH
2	100360	KNOB, BLACK, VOLUME	13	100597	NUT, HEX, 3/8-24, FLEX BOOM ADAPTER	24	100258	CLIP, HEADBAND GUIDE, PLASTIC
3	100365	POTENTIOMETER, 2K	14	100603	YOKE, EAR CUP MOUNT, METAL, BLACK	25	100393	CLIP, ANTI-ROTATION, YOKE, PLASTIC
4	100079	RECEIVER, 300 OHM, MONO	15	100569	STRAIN RELIEF, CABLE	26	100613	HEADBAND, METAL, BLACK, LARGE
5	100108	SCREW, 4-40 X 1/4, THREAD FORMING	16	100402	EAR SEAL, GEL FILLED	27	100604	BRACKET, YOKE SUPPORT WITH TANG, BLACK
6	800193	MICROPHONE & FLEX BOOM ASSEMBLY	17	100370	RECEIVER MOUNT, HEADSET	28	800118	HEAD PAD ASSEMBLY, SIDE, WITH CUSHION, S-18
7	100251	E-RING, EAR CUP TO YOKE RETAINER	18	900111	WINDSCREEN, MIC, 8 SERIES	29	100579	CLIP, CLOTHING, HEADSET CABLE
8	100252	NUT, HEX, 8-32, LOCKING	19	100373	SLIDE, YOKE BRACKET, LONG, NYLON	30	100610	CUSHION, HEADBAND, FOAM FILLED
9	100401	EAR CUP, PRINTED AND DRILLED	20	100374	FOAM, SOUND ATTENUATING. NOTCHED, 1/2 INCH	31	100602	OPTIONAL - HEADBAND, METAL, BLACK, STANDRD
10	100619	HEAD BAND EXTRUSION, 6.25 IN., S-18	21	100376	FOAM, SOUND ATTENUATING. RECEIVER HOLE, 1/2 INCH	32	100672	OPTIONAL - HEADBAND, METAL, BLACK, YOUTH
11	100363	SCREW, 8-32 X 1/2, PHILLIPS HEAD	22	800036	CABLE, HEADSET, MONAURAL	33	100369	OPTIONAL - EAR SEAL, FOAM FILLED